



ATTORNEY'S DOCKET HIR-115
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the application of:) Group Art Unit: 1773
)
KARAIWA) Examiner: JACKSON, M. R.
)
Serial No. 09/649,092)
)
Filed: August 28, 2000)

For: **THERMOPLASTIC ELASTOMER LAMINATED MATERIAL**

APPENDIX A

Please amend the following claims as indicated in the following marked-up copy of the claims.

1. (Twice Amended) A laminated material comprising:

- (i) a surface layer comprising a polyolefinic thermoplastic elastomer (A) containing an oily softening agent, and
- (ii) an underlayer comprising a polyolefinic thermoplastic elastomer (B) containing an oily softening agent which underlayer is laminated on the surface layer,

wherein the ratio (a) of the oily softening agent to an amorphous component, or if [the] polyethylene is incorporated, to the total of an amorphous component and

RECEIVED
SEP 19 2002
TC 1700

polyethylene in said thermoplastic elastomer (A) and the ratio (b) of the oily softening agent to an amorphous component, or if [the] polyethylene is incorporated, to the total of an amorphous component and polyethylene in said thermoplastic elastomer (B) satisfy the following requisites;

ratio(a) \geq [0.8 X] ratio (b),

ratio(a) = 5 to 62.5 wt.%, and

ratio(b) = 5 to 62.5 wt.%.



ATTORNEY'S DOCKET HIR-115
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the application of:) Group Art Unit: 1773
)
KARAIWA) Examiner: JACKSON, M. R.
)
Serial No. 09/649,092)
)
Filed: August 28, 2000)

For: **THERMOPLASTIC ELASTOMER LAMINATED MATERIAL**

APPENDIX B

Please amend the following claims as indicated in the
following clean copy of the claims.

RECEIVED
SEP 19 2002
TC 1700

Subcl

1. (Twice Amended) A laminated material
comprising:
 (i) a surface layer comprising a polyolefinic
 thermoplastic elastomer (A) containing an
 oily softening agent, and
 (ii) an underlayer comprising a polyolefinic
 thermoplastic elastomer (B) containing an
 oily softening agent which underlayer is
 laminated on the surface layer,
wherein the ratio (a) of the oily softening agent to
an amorphous component, or if polyethylene is incorporated,

Sub C1
cont. → to the total of an amorphous component and polyethylene in
said thermoplastic elastomer (A) and the ratio (b) of the
oily softening agent to an amorphous component, or if
polyethylene is incorporated, to the total of an amorphous
component and polyethylene in said thermoplastic elastomer
(B) satisfy the following requisites;

$\text{ratio}(a) \geq \text{ratio}(b),$

$\text{ratio}(a) = 5 \text{ to } 62.5 \text{ wt.}\%, \text{ and}$

$\text{ratio}(b) = 5 \text{ to } 62.5 \text{ wt.}\%.$
